

**COMPRESSOR DATA SHEET**  
**Rotary Compressor: Variable Frequency Drive**



**MODEL DATA - FOR COMPRESSED AIR**

1	Manufacturer: <b>ELGi</b>		
2	Model Number: <b>EG 22V-100</b>	Date: <b>11/06/2017</b>	Type: <b>SCREW</b>
	<input checked="" type="checkbox"/> Air-cooled <input type="checkbox"/> Water-cooled	# of Stages: <b>1</b>	
	<input checked="" type="checkbox"/> Oil-injected <input type="checkbox"/> Oil-free		
3	Rated Operating Pressure	<b>100</b>	psig <sup>b</sup>
4	Drive Motor Nominal Rating	<b>30</b>	hp
5	Drive Motor Nominal Efficiency	<b>93.6</b>	percent
6	Fan Motor Nominal Rating (if applicable)	<b>0.39 X 2</b>	hp
7	Fan Motor Nominal Efficiency	<b>NA</b>	percent
8*	Input Power (kW)	Capacity (acfm) <sup>a,d</sup>	Specific Power (kW/100 acfm) <sup>d</sup>
	<b>26.8</b> Max	<b>140.0</b>	<b>19.13</b>
	<b>25.5</b>	<b>125.0</b>	<b>20.37</b>
	<b>23.3</b>	<b>113.0</b>	<b>20.66</b>
	<b>21.1</b>	<b>100.0</b>	<b>20.97</b>
	<b>17.7</b>	<b>82.0</b>	<b>21.50</b>
9*	<b>14.4</b> Min	<b>65.0</b>	<b>22.14</b>
	Total Package Input Power at Zero Flow <sup>c, d</sup>	<b>0.00</b>	<b>kW</b>
10	<p>Note: Graph is only a visual representation of the data in Section 8          Note: Y-Axis Scale, 10 to 35, + 5kW/100acfm increments if necessary above 35          X-Axis Scale, 0 to 25% over maximum capacity</p>		

\*For models that are tested in the CAGI Performance Verification Program, these items are verified by program administrator

Consult CAGI website for a list of participants in the third party verification program: [www.cagi.org](http://www.cagi.org)

NOTES:

- Measured at the discharge terminal point of the compressor package in accordance with ISO 1217, Annex E; acfm is actual cubic feet per minute at inlet conditions.
- The operating pressure at which the Capacity and Electrical Consumption were measured for this data sheet.
- No Load Power. In accordance with ISO 1217, Annex E, if measurement of no load power equals less than 1%, manufacturer may state "not significant" or "0" on the test report.
- Tolerance is specified in ISO 1217, Annex E, as shown in table below:

NOTE: The terms "power" and "energy" are synonymous for purposes of this document.



Volume Flow Rate at specified conditions		Volume Flow Rate	Specific Energy Consumption	No Load / Zero Flow Power
m <sup>3</sup> / min	ft <sup>3</sup> / min	%	%	
Below 0.5	Below 15	+/- 7	+/- 8	+/- 10%
0.5 to 1.5	15 to 50	+/- 6	+/- 7	
1.5 to 15	50 to 500	+/- 5	+/- 6	
Above 15	Above 500	+/- 4	+/- 5	

ROT 031

10/11 R7

This form was developed by the Compressed Air and Gas Institute for the use of its members. CAGI has not independently verified the reported data.